

## TRACK FOR SURFACE OR SUSPENSION MOUNTING

**Typology**
3-phase rail in extruded aluminium painted black or white.
Grey unpainted anodised aluminium finish available on request.

**Features**
Ease of use: always observe the earthing line.
Extensive accessories options to create ever different and surprising track systems: flexible curves, T, L and X elements.
Allows for 3 differentiated switching.

**Installation**
Surface or suspension installation.

**Power supply**
Frequency: 50 Hz.
Current and voltage rating: L1/L2/L3/N/ground 16A/250V.
Load on phase: 3.6kVA.
On the 3 phases: 3X 3.6kVA.

### Characteristic data

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Color | Black | | | | | | |

### Dimensional characteristics

| | |
|---|---|
| L | 1030 mm |
| L1 | 36 mm |
| H | 33 mm |

### Logistics data

| | |
|---|---|
| Item net weight | 1100 gr |
| Barcode single item | 8011905330576 |
| Minimum order quantity | 1 |
| Minimum packaging | 1 / 1 |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products