



QUADRIPACK A60

Typology

LED lamps in convenient 4-piece packs.

Features


The same quality as other lamps, optimised packaging.



Characteristic data

Power	11 W	Beam	220°	Dimmable	No	Input	220-240 Vac
Base	E27	IP	20	Flux	1087 lm	PF	0,5
Tc	6400 K	Ra	80	LED Warranty	G2		

Dimensional characteristics



Ø	60 mm
H	120 mm
H Tolerance	± 3 mm

Lighting and photometric features

Beam opening	220°
Flux	1087 lm
CCT nominal colour temperature	6400 K
Colour of the light	Cool light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	11 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,5
Energy efficiency class	F
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	77
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	100 gr
Barcode single item	8011905982577
Number of pieces multiple pack	24
Minimum order quantity	6
Minimum packaging	6 / 24

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products