

PRO | 220-240 Vac | Ra >80 | 50000 h L80B20

IP20 VI IP43 VO | Free Wire | -20°C +45°C | Risk Group 0 | UGR <19

FLICKER FREE | G5 h24

SLIMFLUX BL UGR - PRO

Typology
Ultra-flat LED fixtures with lateral lighting.
Driver NOT included, to be fitted with the suitable driver.
Equipped with steel anti-fall safety cable.

Features
Side heat dissipation.
Immediate switch-on.
Colour rendering: Ra>80.
Do not use with dimmer.
If you want to dim or use the multicurrent power supply dimmer.
UGR version.
Class II fittings.
The use of the dimmable 1-10V driver, code DELT40D-10V, or DALI, code A01486, set at 550mA, makes the luminaire compliant with Italian Ministerial Decree of 24 November 2025 (CAM – Minimum Environmental Criteria for public buildings) L90B10 - 50000h.

Installation
Installations: recessed, suspended, ceiling/wall.
Surface mounting & adjustable suspension wire kits are available as accessories.

Material
Body with white finish.
Anti-yellowing PS screen.

Usage information
SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

Emergency
SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.


Packaging
BL model: 6 pieces pack with single items' box.

Characteristic data

Power	28 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Optical compartment IP	43	Flux	3600 lm	PF	- -
UGR	<19	Tc	4000 K	Ra	>80	LED Warranty	G5h24
RG	RG0						

Technisches Datenblattsheet
Fiche technique
Ficha de datos
Technical datasheet
Scheda tecnica

Dimensional characteristics



L	595 mm
L1	595 mm
H	35 mm

Lighting and photometric features


Flux	3600 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L80B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<19

Electrical characteristics

Rated power	28 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	- -
Max output current	700 mA
Operating temperature	-20°C / +45°C

Other Infotech

Flicker Free	Yes
Light source replaceability	Replaceable (LED only) light source by a professional.



LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	2150 gr
Barcode single item	8011905003784
Number of pieces multiple pack	6
Minimum order quantity	1
Minimum packaging	1 / 6

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products