



EMERGENCY ELECTRONIC UNIT FOR STANDBY LIGHTING

Typology

Emergency electronic unit for standby lighting (as indicated by the UNI EN 1838) suitable for current controlled power LED.

Can be used for maintained or emergency operation.

Can be used with max 2A - 90V.



Battery life: 3 hours (battery pack dimensions: 135 x 45 x 23 mm).

Battery inserted in a protective case in accordance with regulations.

Residual flux in emergency 7%.

Reserve lighting means lighting that allows you to continue normal activity without substantial change.

Fixtures indicated as compatible with the kit have passed the required tests for the reserve lighting category in compliance with EN 60598-2-22.



Characteristic data

Input	220-240 Vac	Base	Screws	IP	20		
-------	-------------	------	--------	----	----	--	--

Dimensional characteristics

L	150 mm
L1	40 mm
H	29 mm

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Output voltage	85 Vdc
Operating temperature	5°C / +45°C

Other Infotech

Max Case Temperature	75
----------------------	----

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61347-1:2016 (+A1:2021)
 CEI EN 61347-2-13:2015 (+A1:2018)
 CEI EN 61547:2010

Logistics data

Item net weight	160 gr
Barcode single item	8011905355876
Number of pieces multiple pack	10
Minimum order quantity	1
Minimum packaging	1 / 10