



STAGNA S1T L2 IP65

Typology

Waterproof linear ceiling light with G13 base for 1 TUBOLED.
Tube not included.

Features

Quick opening mechanism for wiring.
Designed to withstand dust and water jets.

Installation


"Snap on" AISI 316 stainless steel brackets for ceiling or suspension installation.
Every batten is equipped with brackets.

Material

Polycarbonate body and transparent polycarbonate screen.

Applications


Supermarkets, car parks, laboratories, warehouses.



Characteristic data

Dimmable	No	Input	220-240 Vac	Base	G13	IP	65
LED Warranty	G2	IK	IK07				

Dimensional characteristics



L	1575 mm
L1	65 mm
H	60 mm

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Operating temperature	-25°C / +35°C

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	690 gr
Barcode single item	8011905015145
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10