



## DECO LED HIGH POWER HP2

### Typology

Range of high power LED lamps with SMD technology and high efficiency chip.

### Features

Flux up to 8600 lumens to replace also discharge lamps.  
PF: 0.95~97.

### Installation

Ne pas utiliser dans des appareils fermés ou sans circulation d'air.

### Material

Heat-resistant plastic body with metal inner coating; opaline anti-glare polycarbonate cover.

### Usage information

In order to replace discharge lamps with Deco Led High Power: make sure the fitting is suitable for direct feeding from the mains.  
Do not use in enclosed fixtures or without air circulation.  
Do not use with dimmer.

### Notes


In case of installation in public areas, it is advisable to use overvoltage surge protection.  
The HP2 models are designed to withstand voltage peaks up to 6KV.



### Characteristic data

Power	70 W	Beam	200°	Dimmable	No	Input	220-240 Vac
Base	E40	IP	20	Flux	10000 lm	PF	0,97
Tc	6400 K	Ra	>80	LED Warranty	G2		

### Dimensional characteristics



Ø	137 mm
H	250 mm
H Tolerance	± 3 mm

## Lighting and photometric features

Beam opening	200°
Flux	10000 lm
CCT nominal colour temperature	6400 K
Colour of the light	Cool light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

## Electrical characteristics

Rated power	70 W
Input voltage	220-240 Vac
Dimmable	No
Power factor (PF)	0,97
Weighted energy consumption	70 kWh/1000h
Energy efficiency class	D
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	527

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60968:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62560:2013 (+A1:2017/+A11:2020)  
CEI 34-141:2014

## Logistics data

Item net weight	600 gr
Barcode single item	8011905987763
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products