



OPTIONAL ASYMMETRICAL LENS

Optional ASYMMETRICAL lens for universal profiles

-25°C
+35°C

Dimensional characteristics

| | |
|---|---------|
| L | 2000 mm |
|---|---------|

Electrical characteristics

| | |
|-----------------------|---------------|
| Operating temperature | -25°C / +35°C |
|-----------------------|---------------|

Photometry

| | 3000K | H(m) | D1(m) | D2(m) | E _{max} (lx) | | |
|---------------|-----------------------------|------------------|-------|-------|-----------------------|-------|----|
| | Ra95 | | 89° | 92° | | | |
| Fixture Power | 12W | 1 | 1.97 | 2.07 | 422 | | |
| Source Flux | 860lm | 2 | 3.95 | 4.14 | 106 | | |
| Fixture Flux | 860lm | 3 | 5.92 | 6.21 | 47 | | |
| Efficacy | 72lm/W | 4 | 7.90 | 8.28 | 26 | | |
| 933128 | I _{max} =498cd/klm | I _{max} | 428cd | 5 | 9.87 | 10.35 | 17 |

EulumDat file on the site

European Directives

| | |
|---|--|
| 2011/65/EU * RoHS 2015/863 * Amending RoHS | |
|---|--|

Logistics data

| | |
|--------------------------------|---------------|
| Item net weight | 130 gr |
| Barcode single item | 8011905933128 |
| Number of pieces multiple pack | 5 |
| Minimum order quantity | 5 |
| Minimum packaging | 5 / 5 |