

EUROSTANDARD PLUS - RECESSED

Eurostandard Plus track from the Targetti collection.
System is a 3 phase mixed system with two additional conductors intended to manage a general data signal (for example DALI, DMX).
Electrified track in three lengths in extruded anodized aluminum or in extruded painted aluminium.
Conductors in copper insulated in PVC.

Installation
There are three possible installation systems: directly on false ceiling (using the needlepoints on the track and the suspension kit), on ceiling using a metal clip or hanging by a mounting kit.

Power supply
Frequency: 50 Hz.
Rated current and voltage: L1/L2/L3/N/ground 16A/440V + D+/D- 2x1A/50V FELV AC (DALI).
Phase / phases power: 3,6kVA / 10,8kVA.


230-280 Vac

G5 h24

Characteristic data

Input	230-280 Vac	LED Warranty	G5h24	Color	Black		

Dimensional characteristics



L	1000 mm
L1	52 mm
H	37.8 mm

Electrical characteristics

Input voltage	230-280 Vac

Technisches Datenblattsheet
Fiche technique
Ficha de datos
Technical datasheet
Scheda tecnica

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.

European Directives

2011/65/EU * RoHS 2012/19/EU * RAEE 2015/863 * Amending RoHS	

Logistics data

Item net weight	1100 gr
Barcode single item	8011905992484
Minimum order quantity	1
Minimum packaging	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products