

SLIMFLUX TRANSLUCENT UP&DOWN - PLUS

Typology
Translucent LED panel with double emission, dimmable.


Features
Fixture with visual interest characterised by dual emission - 70% downwards and 30% upwards - along with the translucency of the panel itself.


Material
Body with white finish.
Frontal methacrylate panel.

Power supply
The luminaire comes complete with a remote power supply integrated into one of two white metal parallelepipeds to be fixed to the ceiling.

Notes
Adjustable suspension wires: MAX 150 cm.
Cable attachment with screw and steel cylinder.

Connections
Use 0-10V dimmers.






PLUS | 220-240 Vac | Ra 80 | 0-10V | 30000 h L70B20 | IP20 | Free Wire | -25°C +40°C | Risk Group 0 | UGR <19

120° | FLICKER FREE | G3

Characteristic data

Power	40 W	Beam	120°	Dimmable	0-10V	Input	220-240 Vac
Base	Free Wire	IP	20	Flux	3800 lm	PF	0.95
UGR	<19	Tc	3000 K	Ra	80	LED Warranty	G3
RG	RG0						

Dimensional characteristics



L	1200 mm
L1	300 mm
H	14.5 mm


Lighting and photometric features

Beam opening	120°
Flux	3800 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	30000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<19

Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	0-10V
Power factor (PF)	0.95
Operating temperature	-25°C / +40°C

Photometry



984304 Imax=171cd/klm

4000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra80			150°	132°	
Fixture Power	40W	1	7.40	4.45	458
Source Flux	3800lm	2	14.80	8.89	115
Fixture Flux	3800lm	3	22.20	13.34	51
Efficacy	95lm/W	4	29.61	17.78	29
Imax	650cd	5	37.01	22.23	18

EuLumDat file on the site

Other Infotech

Flicker Free	Yes

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	3500 gr
Barcode single item	8011905984298
Number of pieces multiple pack	5
Barcode multiple pack	8011905985721
Minimum order quantity	1
Minimum packaging	1 / 5

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products