

DURABLE PENDANT FOR GU10

Typology
Pendant luminaire for direct lighting, for replaceable lamp with GU10 socket.
Round rosette for ceiling installation.

Features
Minimal, simple design and precise finishing.
Available in different size and colours.

Material
Die-cast painted aluminium body.

Beam
Can be used with all GU10 lamps in the catalogue: select the desired power and beam opening.


Notes
Cable lenght 1,5 m.

PLUS | 220-240 Vac | IP20 | GU10 | -15°C +35°C

Characteristic data

Input	220-240 Vac	Base	GU10	IP	20	Color	White

Dimensional characteristics



ø	60 mm
H	150 mm

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Operating temperature	-15°C / +35°C

European Directives	Product standards
2009/125/EC * Ecodesign	CEI EN 55015:2020 (+A11:2020)
2011/65/EU * RoHS	CEI EN 60598-1:2022
2012/19/EU * RAEE	CEI EN 60598-2-2:2012
2014/30/EU * EMC	CEI EN 61000-3-2:2019 (+A1:2021)
2014/35/EU * LVD	CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
2015/863 * Amending RoHS	CEI EN 61547:2010
2017/1369 * Regulation for Energy Labelling	CEI EN 62031:2021 (+A11:2022)
2019/2015 * Regulation for Energy Labelling	CEI EN 62471:2010
2019/2020 * Regulation for Ecodesign	IEC/TR 62471-2:2009
2021/340 * Amending Reg. Energy Labelling	CEI EN 62493:2015
2021/341 * Amending Reg. Ecodesign	CEI 34-141:2014

Logistics data

Item net weight	313 gr
Barcode single item	8011905980573
Number of pieces multiple pack	20
Minimum order quantity	1
Minimum packaging	1 / 20

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products