



COMPACT MULTI CCT

Multifunction recessed LED fittings for a 50 mm cut-out.

Typology

This model offers selectable colour temperature (2700-3000-4000K) and allows you to choose between four beam angles (18°-26°-36°-50°).
Selection switches positioned on the remote driver.
Beam angle adjustment via side sliders.
Supplied with round bezel.
Optional square ring, easy to install, see accessory code.

Installation

Equipped with steel springs for installation in false ceilings.

Material

Body in die-cast aluminium.

Applications

Thanks to their application flexibility, these fixtures are particularly suitable for responding to changing visual needs over time: product displays, retail interiors, shop windows.

Notes


The flux data indicated refers to the 4000K colour temperature and 26° beam opening. For additional data, see the QR code.



Characteristic data

Power	11 W	Beam	18-26-36-50	Dimmable	No	Input	220-240 Vac
Base	Free Wire	IP	20	Flux	950 lm	Axis	3850 cd
PF	0.9	Tc	2700-3000-4000 K	Ra	>90	LED Warranty	G4
RG	RG1						

Dimensional characteristics



Ø	60 mm
H	70 mm

Cutting hole	50
--------------	----

Lighting and photometric features

Beam opening	18-26-36-50
Flux	950 lm
Axis	3850 cd
CCT nominal colour temperature	2700-3000-4000 K
Colour of the light	CCT
Colour rendering index	>90
Lifespan	25000 h
LED lifespan	L70B50
Luminous Flux Maintenance at 2000h	10

Electrical characteristics

Rated power	11 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0.9
Energy efficiency class	This product contains a light source of energy efficiency class "F"
Operating temperature	-25°C / +35°C

LED Warranty

G4	undefined
----	-----------

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-2:2012
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Item net weight	174 gr
Barcode single item	8011905345891
Number of pieces multiple pack	10
Minimum packaging	1 / 60