



EVO DAMP PROOF LUMINAIRE FOR 2 T8 LED TUBES

Typology

Waterproof linear ceiling light for 2 TUBOLED, G13 base.
Equipped with reflector for optimising light emission.
LED tubes not included, do not use with fluorescent tubes.

Features

IP65 cable gland at the input for quick wiring.
IK07 mechanical impact protection rating.

Installation


Each package is equipped with stainless steel snap-on brackets for ceiling mounting or suspension.

Material

Body and screen closing clip in ABS.
Transparent polycarbonate screen equipped with internal fins for optimization of light emission.

Applications


Supermarkets, car parks, laboratories, warehouses.



Characteristic data

Dimmable	No	Input	220-240 Vac	Base	G13	IP	65
LED Warranty	G2	IK	IK07				

Dimensional characteristics



L	1570 mm
L1	95 mm
H	52 mm

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Operating temperature	-25°C / +35°C

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-1:2022
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Barcode single item	8011905345419
Number of pieces multiple pack	9
Barcode multiple pack	8011905345822
Minimum order quantity	9
Minimum packaging	9 / 9