



DURANEONFLEX VERT

Uniform and flexible light

Ready-to-light

DuraNeonFlex is a flexible extruded silicone profile, complete with 120 LEDs per meter strip.

The narrow pitch of the chips and Integrated Circuit technology make DNF a perfect light line, homogenous on all its 10 meters of length.

What's best ... it is ready-to-light!

Typology

Flexible light line with uniform emission in two directions depending on the model. The section of the profile can be rounded or squared.

Both models have a TOP and VERT versions.

Features

Flexible light line with continuous lighting: so flexible you can create curves with a minimum diameter of 12 cm.

TOP flex Version: the light is emitted on the upper side of the light channel.

VERT flex Version: vertical emission away from the bottom of the channel.

Anti-glare diffuser function.

Maximum length per single power supply: 10 metres.

Installation

It is attached to the surface with the clips; it can be cut following the cutting marks (5cm).

Fitted with different outputs for power supply.

Installation temperature: 0° ~ 35°C; working temperature: -25° +35°C.

Material

Extremely flexible, impact resistant and weatherproof extruded silicone. Minimum colour shift compared to the colour of the chip.

Usage information

Dimmable 0-100%

DALI - DMX

Analogue and digital domotic control systems

Push Dali with ZKCOAFF controllers

CASAMBI compatible

Power supply

Max current for single power supply: 4A.

Packaging

Available to order with minimum quantities to be agreed on with the sales force.

DNF can be supplied at any specific length (max length 10 meters for single power supply, cut every 5 cm) with or without the electrical terminals or in 10 m and 50 m reels without terminals.

Colour of the light

Range of white and pure colours both with 120 LED per meter.

RGB version available on DNF and DNF-Q models.

PLUS	24 Vdc	Ra 80		36000 h L70B20
IP65	IK07	Free Wire	-25°C +35°C	Risk Group 0
	150°			

Characteristic data

Power	90 W	Beam	150°	Dimmable	Yes	Input	24 Vdc
Base	Free Wire	IP	65	Flux	4000 lm	Tc	3000 K
Ra	80	LED Warranty	G4h24	IK	IK07	RG	RG0

Dimensional characteristics



L	10000 mm
L1	8.8 mm
H	20 mm

Cutting pitch	50 mm
LED pitch	50 mm

Lighting and photometric features

Beam opening	150°
Nominal flux per mt	400 lm/m
Flux	4000 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	36000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	90 W
Input voltage	24 Vdc
Dimmable	Yes
Energy efficiency class	This product contains a light source of energy efficiency class "F"
Operating temperature	-25°C / +35°C
Operating position	360°

Photometry

	3000K	H(m)	D1(m)	D2(m)	Emax(lx)		
	Ra80		137°	171°			
	Fixture Power	9W	1	5.10	25.47	81	
	Source Flux	400lm	2	10.19	50.94	20	
	Fixture Flux	400lm	3	15.29	76.41	9	
	Efficacy	44lm/W	4	20.38	101.88	5	
	09UV240930-Bmax=203cd/klm	Imax	81cd	5	25.48	127.35	3

EulumDat file on the site

LED Warranty

G4h24	Full Guarantee 4 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	1935 gr
Barcode single item	8011905909048
Minimum order quantity	1
Minimum packaging	1 / 1