



STAGNA S1T L2 IP65 - 50000H

Typology

Waterproof linear ceiling light with G13 base for 1 TUBOLED.
Complete with 50,000h Tuboled.

Features

Quick opening mechanism for wiring.
Designed to withstand dust and water jets.

Installation

"Snap on" AISI 316 stainless steel brackets for ceiling or suspension installation.
Every batten is equipped with brackets.

Material

Polycarbonate body and transparent polycarbonate screen.

Applications


Supermarkets, car parks, laboratories, warehouses.



Characteristic data

Power	18 W	Dimmable	No	Input	220-240 Vac	Base	G13
IP	65	Flux	1475 lm	PF	0,9	Tc	3000 K
Ra	>80	LED Warranty	G4	IK	IK07	RG	RG0

Dimensional characteristics



L	1275 mm
L1	65 mm
H	60 mm

Lighting and photometric features

Flux	1475 lm
CCT nominal colour temperature	3000 K
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L70B50

Electrical characteristics

Rated power	18 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,9
Operating temperature	-25°C / +35°C

Photometry

EulumDat file on the site

LED Warranty

G4	undefined
----	-----------

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-1:2022
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Item net weight	780 gr
Barcode single item	8011905017019
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products