



LED DRIVER

Features

Driver for LED strips.
SELV equivalent; protection device in case of short circuit or overload in the secondary circuit.
24V drivers have loose wires connection and are TUV marked.
150W SL drivers are fit for use inside aluminium profiles where indicated.



Characteristic data

Power	150 W	Dimmable	No	Input	110-260 Vac	Base	Free Wire
IP	20	PF	0,9	LED Warranty	G5h24		

Dimensional characteristics

L	330 mm
L1	32 mm
H	22 mm

Lighting and photometric features

Lifespan	50000 h
----------	---------

Electrical characteristics

Rated power	150 W
Input voltage	110-260 Vac
Frequency	50 Hz
Output voltage	24 Vdc
Dimmable	No
Power factor (PF)	0,9
Input current	6.3 A
Operating temperature	-20°C / +45°C

Other Infotech

Flicker Free	Yes
Max Case Temperature	85

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61347-1:2016 (+A1:2021)
 CEI EN 61347-2-13:2015 (+A1:2018)
 CEI EN 61547:2010

Logistics data

Item net weight	310 gr
Barcode single item	8011905000776
Minimum order quantity	1
Minimum packaging	1 / 1