



QUADRIPACK A60

Typology

LED lamps in convenient 4-piece packs.

Features

The same quality as other lamps, optimised packaging.




BASIC	220-240 Vac	Ra 80		15000 h L70B50	IP20	E27	-25°C +35°C		

Characteristic data

Power	13.5 W	Beam	200°	Dimmable	No	Input	220-240 Vac
Base	E27	IP	20	Flux	1552 lm	PF	0,7
Tc	4000 K	Ra	80	LED Warranty	G2		

Dimensional characteristics



Ø	60 mm
H	120 mm

Lighting and photometric features

Beam opening	200°
Flux	1552 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	13.5 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,7
Input current	0.08 A
Energy efficiency class	E
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	102
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60968:2016
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62560:2013 (+A1:2017/+A11:2020)
 CEI 34-141:2014

Logistics data

Item net weight	160 gr
Barcode single item	8011905973674
Number of pieces multiple pack	24
Barcode multiple pack	8011905973957
Minimum order quantity	6
Minimum packaging	6 / 24