



WIRELESS UNIT WITH DALI INTERFACE

A wireless control module with a DALI interface

It generates a local DALI bus which makes it possible to connect a LED driver directly to a DALI interface.

The module can only be used in a closed system and cannot be connected to an existing DALI network.

The module is wireless controlled using a CASAMBI app for smartphones and tablets using Bluetooth 4.0 technology.

The devices create an adaptive, secure and reliable wireless mesh network that can control a large number of fixtures in a simple and efficient way.

One device can be used to control one appliance/strip only.

220-240
Vac

IP20

Terminals

Characteristic data

Power	1.1 W	Input	220-240 Vac	Base	Terminals	IP	20
-------	-------	-------	-------------	------	-----------	----	----

Dimensional characteristics

L	41 mm
L1	37 mm
H	14 mm

Electrical characteristics

Rated power	1.1 W
Input voltage	220-240 Vac

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61347-1:2016 (+A1:2021)
 CEI EN 61347-2-11:2002 (+A1:2020)
 CEI EN 61547:2010

Logistics data

Item net weight	48 gr
Barcode single item	8007753525516
Minimum order quantity	1
Minimum packaging	1 / 1