



## TECNO VINTAGE EVO TRANSPARENT CANDLE

### Typology

Range of lamps "filament LED": micro-led sources - that optimise thermal management - are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

### Features

Excellent colour maintenance and are light constant over time.  
The spectrum of Tecno Vintage lamps is particularly rich in the warm colour bands to obtain an effect as close as possible to that of the lamps to be replaced.

### Material

Glass bulb.



220-240  
Vac



Ra 80



15000 h  
L70B50

E27

-25°C  
+35°C



### Characteristic data

|       |     |              |         |          |      |       |             |
|-------|-----|--------------|---------|----------|------|-------|-------------|
| Power | 7 W | Beam         | 320°    | Dimmable | No   | Input | 220-240 Vac |
| Base  | E27 | Flux         | 1060 lm | PF       | 0.55 | Tc    | 4000 K      |
| Ra    | 80  | LED Warranty | G2      |          |      |       |             |

### Dimensional characteristics

|   |       |
|---|-------|
| Ø | 35 mm |
| H | 93 mm |

### Lighting and photometric features

|                                           |                    |
|-------------------------------------------|--------------------|
| Beam opening                              | 320°               |
| Flux                                      | 1060 lm            |
| CCT nominal colour temperature            | 4000 K             |
| Colour of the light                       | Natural light      |
| Colour rendering index                    | 80                 |
| Lifespan                                  | 15000 h            |
| LED lifespan                              | L70B50             |
| Trigger time                              | <0,2 s             |
| Heating time up to 60% of full efficiency | Instant Full Light |

## Electrical characteristics

|                                    |               |
|------------------------------------|---------------|
| Rated power                        | 7 W           |
| Input voltage                      | 220-240 Vac   |
| Frequency                          | 50/60 Hz      |
| Dimmable                           | No            |
| Power factor (PF)                  | 0.55          |
| Input current                      | 0.055 A       |
| Weighted energy consumption        | 7 kWh/1000h   |
| Energy efficiency class            | D             |
| Number of cycles                   | 100000        |
| Operating temperature              | -25°C / +35°C |
| Equivalence with incandescent lamp | 75            |
| Operating position                 | 360°          |

## LED Warranty

|    |                                                                                                                                                                                        |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| G2 | Up to 2 years<br>(4000h/year) *4000h = 11h a day x 365 days.<br>Without limitations on the duration of use for the first year, provided the observance of the installation conditions. |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60968:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62560:2013 (+A1:2017/+A11:2020)  
CEI 34-141:2014

## Logistics data

|                                |               |
|--------------------------------|---------------|
| Barcode single item            | 8011905346935 |
| Number of pieces multiple pack | 10            |
| Barcode multiple pack          | 8011905349325 |
| Minimum order quantity         | 10            |
| Minimum packaging              | 10 / 10       |