

PRO | 220-240 Vac | Ra >80 | 50000 h L80B20

IP20 VI IP43 VO | Connector | -20°C +45°C | Risk Group 0 | UGR <19

III | FLICKER FREE | G5 h24

SLIMFLUX SL UGR - PRO - NO DRIVER

Typology
Ultra-flat LED fixtures with lateral lighting.
Panels of this range are supplied WITHOUT driver: please select the required driver from the range.

Features
Side heat dissipation.
Immediate switch-on.
Colour rendering: Ra>80.
Do not use with dimmer.
If you want to dim or use the multicurrent power supply dimmer.
UGR version.
Class III fittings.

Installation
Installations: suspended, recessed.
No available frames for surface mounting of the 62x62 panel.
Surface mounting & adjustable suspension wire kits are available as accessories.

Material
Body with white finish; high-transmittance PMMA primary optics.

Usage information
SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

Emergency
SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.


Packaging
SL model: 5 pieces pack with single items' box.

Notes
This panel does NOT inlude the driver: please select the required product from the range.
Providing greater visual comfort, improved definition of detail and reduction of stress.

Characteristic data

Power	33 W	Dimmable	No	Input	220-240 Vac	Base	Connector
IP	20	Optical compartment IP	43	Flux	4350 lm	UGR	<19
Tc	4000 K	Ra	>80	LED Warranty	G5h24	RG	RG0

Dimensional characteristics



L	615 mm
L1	615 mm
H	9 mm

Lighting and photometric features

Flux	4350 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L80B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<19

Electrical characteristics

Rated power	33 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Operating temperature	-20°C / +45°C

Photometry

EuLumDat file on the site

Other Infotech

Flicker Free	Yes

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	3800 gr
Barcode single item	8011905973933
Number of pieces multiple pack	5
Minimum order quantity	1
Minimum packaging	1 / 5

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products