



DURANEONFLEX CORNER BLACK

Typology

Triangular section silicone extrusion: a profile specifically designed to direct light frontally from a horizontal position. The asymmetric light distribution, emitted from the front side of the triangular section, is ideal for installations in furniture, retail displays, and bookshelves.

Features

It can be cut at any point and does not require the use of aluminum profiles. Black body version.

Installation

Surface mounted with clips; can be cut at any point (free cut).

Usage information

Dimmable 0-100%
DALI - DMX
Analogue and digital domotic control systems
Push Dali with ZKCDA controllers
CASAMBI compatible

Power supply

Max current for single power supply: 4A.

Packaging







Packaged in 5 meters reels.

Binning

SDCM <5

Connections

Supplied with free-wire connection on the left side and an end cap on the other. Optional wiring terminals, with in-line or rear output, on the right or left side.



Characteristic data

Power	60 W	Beam	120°x100°	Dimmable	Yes	Input	24 Vdc
IP	54	Tc	3000 K	Ra	90	LED Warranty	G5h24
IK	IK06	RG	RG1	Color	Black		

Dimensional characteristics



L	5000 mm
L1	15.4 mm
H	6.6 mm


Lighting and photometric features

Beam opening	120°x100°
Nominal flux per mt	630 lm/m
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	90
Lifespan	50000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	60 W
Input voltage	24 Vdc
Dimmable	Yes
Energy efficiency class	This product contains a light source of energy efficiency class "F"

Photometry



EuLumDat file on the site

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-1:2022
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Barcode single item	8011905355135
Number of pieces multiple pack	5
Minimum order quantity	5
Minimum packaging	5 / 5