



DOUBLE EMISSION ARCHITECTURAL PROFILE'S ACCESSORY

Typology

Linear architectural profile configurable in direct, indirect emission or both, for high levels of light emission.

Features

The direct emission is configurable with the use of 1 to 4 strips; indirect emission foresees two strips. Compartment inside the profile suitable for the insertion of the power supply and dimmer. Possibility of on/off switching and dimming separate for direct and indirect lighting.

Installation

Mounting on ceiling for unidirectional or suspended for unidirectional or double emission.

Accessories

The aluminium profile is completed, depending on the application chosen, with screens (flat front and rear pair of screens for indirect emission), side closure caps and suspension kit.

For ceiling mounting the rear support is required, code PRDES0-SL, on which the profile can be attached.

-25°C
+35°C

Risk
Group 0

Characteristic data

| | | | | | | |
|----|-----|--|--|--|--|--|
| RG | RG0 | | | | | |
|----|-----|--|--|--|--|--|

Dimensional characteristics

| | |
|---|---------|
| L | 1220 mm |
|---|---------|

Lighting and photometric features

| | |
|---------|------|
| Mercury | 0 mg |
|---------|------|

Electrical characteristics

| | |
|-----------------------|---------------|
| Operating temperature | -25°C / +35°C |
|-----------------------|---------------|

European Directives

| | |
|---|--|
| 2011/65/EU * RoHS 2015/863 * Amending RoHS | |
|---|--|

Logistics data

| | |
|---------------------|---------------|
| Item net weight | 23 gr |
| Barcode single item | 8011905839987 |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products