



## OPTIONAL FLOOD LENS

Optional FLOOD lens for universal profiles

-25°C  
+35°C

### Dimensional characteristics

|   |         |
|---|---------|
| L | 2000 mm |
|---|---------|

### Electrical characteristics

|                       |               |
|-----------------------|---------------|
| Operating temperature | -25°C / +35°C |
|-----------------------|---------------|

### Photometry

|        |                             |                  |       |       |                       |      |    |
|--------|-----------------------------|------------------|-------|-------|-----------------------|------|----|
|        | 3000K                       | H(m)             | D1(m) | D2(m) | E <sub>max</sub> (lx) |      |    |
|        | Ra95                        |                  | 103°  | 38°   |                       |      |    |
|        | Fixture Power               | 12W              | 1     | 2.54  | 0.69                  | 551  |    |
|        | Source Flux                 | 850lm            | 2     | 5.08  | 1.39                  | 138  |    |
|        | Fixture Flux                | 850lm            | 3     | 7.61  | 2.08                  | 61   |    |
|        | Efficacy                    | 71lm/W           | 4     | 10.15 | 2.78                  | 34   |    |
| 933074 | I <sub>max</sub> =659cd/klm | I <sub>max</sub> | 560cd | 5     | 12.69                 | 3.47 | 22 |

EulumDat file on the site

### European Directives

|   |  |
|---|--|
| 2011/65/EU * RoHS<br>2015/863 * Amending RoHS |  |
|---|--|

## Logistics data

|                                |               |
|--------------------------------|---------------|
| Item net weight                | 130 gr        |
| Barcode single item            | 8011905933074 |
| Number of pieces multiple pack | 5             |
| Minimum order quantity         | 5             |
| Minimum packaging              | 5 / 5         |