



PAR30 IP65

Typology

PAR20, 30 and PAR38 IP65, for use in wet and outdoor environments in suitable fixtures.

Features

Using LED lamps provides significant advantages compared to CFL both in terms of improved optical control as well as from the point of view of luminous effect.

Material


Thermoconductive material.

Applications

Commercial or residential installations with particular attention to the areduction of heat, cause of goods discoloration.

Notes


Do not use with dimmer.



Characteristic data

Power	11 W	Beam	38°	Dimmable	No	Input	220-240 Vac
Base	E27	IP	65	Flux	1100 lm	Axis	2300 cd
PF	0,55	Tc	4000 K	Ra	>80	LED Warranty	G2

Dimensional characteristics



Ø	95 mm
H	106 mm

Lighting and photometric features

Beam opening	38°
Flux	1100 lm
Axis	2300 cd
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	20000 h
LED lifespan	L70B50
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	11 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,55
Input current	0.8 A
Weighted energy consumption	11 kWh/1000h
Energy efficiency class	E
Equivalence with incandescent lamp	126

Other Infotech

Reflector	Yes
-----------	-----

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	170 gr
Barcode single item	8011905846695
Number of pieces multiple pack	10
Barcode multiple pack	8011905846701
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products