



## EVO DAMP PROOF LUMINAIRE FOR 1 T8 LED TUBE

### Typology

Waterproof linear ceiling light for 1 TUBOLED, G13 base.  
Equipped with reflector for optimising light emission.  
LED tubes not included, do not use with fluorescent tubes.

### Features

IP65 cable gland at the input for quick wiring.  
IK07 mechanical impact protection rating.

### Installation


Each package is equipped with stainless steel snap-on brackets for ceiling mounting or suspension.

### Material

Body and screen closing clip in ABS.  
Transparent polycarbonate screen equipped with internal fins for optimization of light emission.

### Applications


Supermarkets, car parks, laboratories, warehouses.



### Characteristic data

Dimmable	No	Input	220-240 Vac	Base	G13	IP	65
LED Warranty	G2	IK	IK07				

### Dimensional characteristics



L	657 mm
L1	60 mm
H	52 mm

### Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Operating temperature	-25°C / +35°C

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-1:2022  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Barcode single item	8011905345365
Number of pieces multiple pack	12
Barcode multiple pack	8011905345877
Minimum order quantity	12
Minimum packaging	12 / 12