



RECESSED PROFILES: P055-R

Features

Aluminium profile for recessed installation.
Aluminium profiles allow for a more stable installation, in case of linear installations.
Recommended for indoor and outdoor (protected) applications and for high power strips in order to better heat dissipation.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

30 mm

MAXIMUM POWER:

42W/m

Installation

Recessed.

Steel spring mounting system for recessed ceiling installation from a minimum of 5mm.

Material

Profile in aluminum alloy 6060/6063, anodized 15/20 microns.
UV resistant PC lens.

Accessories

Transparent lenses with 40° beam angle available, opal cover for replacements, and a continuous flexible 20 m lens for installations without visible interruptions.


Packaging

Packaging of the aluminium-colour profile in kit form (code ending with "KIT"): minimum package of 5 bars complete with opal diffuser, 5 pairs of end caps, and 5 pairs of clips.

Characteristic data

Color	Grey				
-------	------	--	--	--	--

Dimensional characteristics



L	2000 mm
L1	70 mm
L2	55 mm
H	35 mm

European Directives

2011/65/EU * RoHS
2015/863 * Amending RoHS

Logistics data

Item net weight	6 gr
Barcode single item	8011905331382
Number of pieces multiple pack	5
Minimum order quantity	1
Minimum packaging	1 / 5