



## EXTENDER IP67

### Extender IP67

Extender IP67 allows for wireless control with a DALI interface. It generates a local DALI bus with the capacity to drive up to 64 fixtures. It can control groups of fixtures in outdoor applications. It prevents any change to the management features provided by the CASAMBI system.

### Terminals

## Characteristic data

Power	2.7 W	Base	Terminals	PF	0,6		
-------	-------	------	-----------	----	-----	--	--

## Dimensional characteristics

L1	150 mm
L3	40 mm

## Electrical characteristics

Rated power	2.7 W
Power factor (PF)	0,6

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61347-1:2016 (+A1:2021)  
CEI EN 61347-2-11:2002 (+A1:2020)  
CEI EN 61547:2010

## Logistics data

Item net weight	500 gr
Barcode single item	8007753525509
Minimum order quantity	1
Minimum packaging	1 / 1