

EMERGENCY ELECTRONIC UNIT FOR STANDBY LIGHTING

Typology

Emergency electronic unit for standby lighting (as indicated by the UNI EN 1838) suitable for current controlled power LED.

Can be used for maintained or emergency operation.

Can be used with max 2A - 90V.


Battery life: 3 hours (battery pack dimensions: 135 x 45 x 23 mm).

Battery inserted in a protective case in accordance with regulations.

Residual flux in emergency 7%.

Reserve lighting means lighting that allows you to continue normal activity without substantial change.

Fixtures indicated as compatible with the kit have passed the required tests for the reserve lighting category in compliance with EN 60598-2-22.



220-240
Vac

25000 h
L70B50

IP20

Screws


-25°C
+35°C



Characteristic data

Input	220-240 Vac	Base	Screws	IP	20	
-------	-------------	------	--------	----	----	--

Dimensional characteristics



L	155 mm
L1	51 mm
H	26 mm

Lighting and photometric features

Lifespan	25000 h
LED lifespan	L70B50

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50 Hz
Output voltage	57 Vdc
Operating temperature	-25°C / +35°C

Other Infotech

Max Case Temperature	80
----------------------	----

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61347-1:2016 (+A1:2021)
 CEI EN 61347-2-13:2015 (+A1:2018)
 CEI EN 61547:2010

Logistics data

Item net weight	470 gr
Barcode single item	8011905971724
Number of pieces multiple pack	10
Barcode multiple pack	8011905781866
Minimum order quantity	1
Minimum packaging	1 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products