



ASYMMETRIC ANGULAR PROFILES: P027

Features

Extruded aluminum profile complete with diffusing polycarbonate cover for corner mounting at 30° or 60° from the surface.

The asymmetrical profile allows you to choose the light direction.

Available in kits with included accessories or as single bars without accessories.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

12 mm

MAXIMUM POWER:

24W/m

Installation

Fixed in place with clips.

Material

Profile in aluminum alloy 6060/6063, anodized 15/20 microns.

UV resistant PC lens.

Packaging


Aluminum-colored profile kit packaging (code ends with "K"): minimum pack of 5 bars with 5 pairs of end caps and 5 pairs of clips.

Single profile codes: available as a single bar to be completed with lens and end caps.

Characteristic data

Color	Black				
-------	-------	--	--	--	--

Dimensional characteristics



L	2000 mm
L1	20 mm
H	16 mm

Logistics data

Barcode single item	8011905344368
Number of pieces multiple pack	5
Minimum order quantity	5
Minimum packaging	5 / 5

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products