

DURANEONFLEX SLIM TRANSLUCID

Typology

Can be cut at any point, perfect for angular installation between wall and ceiling or in showcases and furniture.

Features

These LED strips use a special chip, evolution of the 2835, which allows cutting at every single LED: only 6.25 mm between each light point. Total freedom of installation, even in the smallest details.

Installation

Complete with 3M double-sided tape to attach to the surface.
When using double-sided tape degrease the application surface adequately.

Usage information

Dimmable 0-100% Flicker Free
DALI - DMX - 1-10
Analogue and digital domotic control systems
Push Dali with ZKCOAFF controllers
CASAMBI compatible

Power supply

Max current for single power supply: 4A.

Packaging


Packaged in 5 meters reels.

Binning

SDCM from <3 to <6.

Connections

Equipped with a line/straight connector with free wires.
Accessory required only in case of cutting and new connection.



Characteristic data

Power	45 W	Beam	120°	Dimmable	Yes	Input	24 Vdc
IP	54	Tc	4000 K	Ra	90	LED Warranty	G5h24
IK	IK06	RG	RG1				

Dimensional characteristics



L	5000 mm
L1	6 mm
H	8.5 mm

Lighting and photometric features

Beam opening	120°
Nominal flux per mt	340 lm/m
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	90
Lifespan	50000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	45 W
Input voltage	24 Vdc
Dimmable	Yes
Energy efficiency class	This product contains a light source of energy efficiency class "F"
Operating temperature	-25°C / +35°C

Photometry

	4000K	H(m)	D(m)	Emax(lx)
	Ra90		111°	
Fixture Power	9W	1	2.89	121
Source Flux	340lm	2	5.78	30
Fixture Flux	340lm	3	8.68	13
Efficacy	38lm/W	4	11.57	8
354886 I _{max} =355cd/klm	I _{max}	121cd	14.46	5

EulumDat file on the site

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-1:2022
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Barcode single item	8011905354886
Number of pieces multiple pack	10
Minimum order quantity	1
Minimum packaging	1 / 10