



SURFACE PROFILES: PRAP-U

Features

Aluminium profile for surface installation.
It houses both IP20 and IP68 strips up to 18 mm in width.
Equipped with a compartment to accommodate cables.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

18 mm

Installation

Surface.
Equipped with a compartment to pass cables through.

Material

6063 Aluminium profile with a white PC screen.

Accessories

Every 2 metre bar is complete with 1 set of end caps (with and without holes) and 1 set of mounting clips.


Packaging

Supplied in packages of 5 bars, each one measuring 2 meters complete with screen and accessories.

Spare accessories available with a separate code.
Screens with different beam openings, spot, flood and asymmetrical available to replace the standard screen the profile is equipped with.

-25°C
+35°C

Dimensional characteristics



L	2000 mm
L1	22 mm
H	19.8 mm

Lighting and photometric features

Mercury	0 mg
---------	------

Electrical characteristics

Operating temperature	-25°C / +35°C
-----------------------	---------------

European Directives

2011/65/EU * RoHS 2015/863 * Amending RoHS	
---	--

Logistics data

Item net weight	580 gr
Barcode single item	8011905933036
Number of pieces multiple pack	5
Minimum order quantity	5
Minimum packaging	5 / 5