

DRIVER DALI

Features

Driver for LED strips.
SELV equivalent; protection device in case of short circuit or overload in the secondary circuit.
24V drivers have loose wires connection.

Power supply

Dimmable Driver Compatibility.
Prior to installation, verify the compatibility between the dimmable driver and the lighting control and automation system used in the installation.
Certain analog, digital, or building automation systems may present functional limitations or compatibility issues that shall be evaluated in advance to ensure proper system operation.



100-277



70000 h

IP67

-20°C
+45°C



Characteristic data

Power	250 W	Dimmable	DALI	Input	100-277	IP	67
LED Warranty	G5h24						

Dimensional characteristics

L	199 mm
L1	63 mm
H	37 mm

Lighting and photometric features

Lifespan	70000 h
----------	---------

Electrical characteristics

Rated power	250 W
Input voltage	100-277
Frequency	50/60 Hz
Output voltage	24
Dimmable	DALI
Operating temperature	-20°C / +45°C

Other Infotech

Max Case Temperature	75
----------------------	----

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61347-1:2016 (+A1:2021)
CEI EN 61347-2-13:2015 (+A1:2018)
CEI EN 61547:2010

Logistics data

Item net weight	857 gr
Barcode single item	8011905357351
Minimum packaging	1 / 1