


SLIMFLUX BL PLAFO - PLUS

Typology
LED panel or direct lighting complete with a ceiling-mounted frame for surface installation.
Also available in a UGR version.

Features
Fixtures can be also be surface mounted both vertically and horizontally.
The positioning of the LED sources on a horizontal plate ensures lighting uniformity on the screen surface and excellent efficiency levels.
If you want to dim or use the multicurrent power supply dimmer.
Colour rendering: Ra>80.

Material
Body with white finish; high-transmittance PMMA primary optics.

Usage information
SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

Emergency
SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.


Notes
Providing greater visual comfort, improved definition of detail and reduction of stress.

PLUS | 220-240 Vac | Ra >80 | 35000 h L70B20 | IP20 VI IP43 VO | Free Wire | -25°C +35°C | Risk Group 0 | FLICKER FREE | G3

Characteristic data

Power	40 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Optical compartment IP	43	Flux	4000 lm	PF	0,95
Tc	4000 K	Ra	>80	LED Warranty	G3	RG	RG0

Dimensional characteristics



L	600 mm
L1	600 mm
H	40 mm


Lighting and photometric features

Flux	4000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	35000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,95
Number of cycles	100000
Operating temperature	-25°C / +35°C

Photometry





4000K		H(m)	D(m)	Emax(lx)
Ra80			115°	
Fixture Power	40W	1	3.11	1361
Source Flux	4000lm	2	6.22	340
Fixture Flux	4000lm	3	9.33	151
Efficacy	100lm/W	4	12.45	85
Imax	1361cd	5	15.56	54

EuLumDat file on the site

Other Infotech

Flicker Free	Yes
Light source replaceability	Replaceable (LED only) light source by a professional.
Control gear replaceability	Replaceable control gear by a professional.





LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	1850 gr
Barcode single item	8011905951238
Number of pieces multiple pack	5
Barcode multiple pack	8011905951795
Minimum order quantity	1
Minimum packaging	1 / 5

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products