



DURAstrip Hivolt Arch Dimmable - 230V

Typology

Mains voltage strip, dimmable.

Features

Dimmable version supplied with TRIAC soft dimming achieved with the built in control Chip.

Strip protected from over voltage & and overheating failure in each 2.30 cm strip segment.

System features miniature electrical connections and a closing end cap similar to the main strip.

Supplied already cut and wired in the requested measurement, may be provided with IP40 or IP65 rating depending on the installation environment.

WARNING: the cutting pitch is 203 mm.

Installation

We recommend to order the assembly clips considering to use 4 clips for every metre. Any particular requests will be specified in the project form.

Material

Fitted with latest generation weatherproof and UV resistant Extruded PVC body for exterior use. Finished with white base and sides along with a transparent upper screen for a clean light emission.

Usage information

230V: TRIAC dimmable, trailing edge 10-100%.

Consult the list of compatible dimmers.

120V: Dimmable ELV 10-100%

Accessories

PC clip for anchoring.

Packaging

Supplied already cut to measures.

Complete with a cable of 1.50 m (black) equipped with a Schuko plug (full collar Schuko IP44) or supplied with free wires (IP65).

LED

Lifetime: internal use >50,000h; external use>35,000h

Colour of the light

Choice of white colour temperatures.

Binning

ANSI/SDCM: 3 step 1 bin.

Connections

Up to 50 metres with a single power supply.



220-240
Vac

Ra 90




35000 h
L70B20

IP40/65

Connector
/ Free terminals

-25°C
+35°C

Risk
Group 0




Characteristic data

Power	12 W	Beam	110°	Dimmable	Yes	Input	220-240 Vac
Base	Connector/Free terminals	IP	40/65	Tc	4000 K	Ra	90
LED Warranty	G3	RG	RG0				


Dimensional characteristics

DURASTRIP HiVolt ARCH DIMMABLE - 230V - IP40 Terminal "IN" with Schuko plug or free wires



FREE WIRES

DURASTRIP HiVolt ARCH DIMMABLE - 230V - IP65 Terminal "EX" with Schuko plug or free wires



L	1000 mm
L1	16.5 mm
H	7 mm

Cutting pitch	203 mm
---------------	--------

Lighting and photometric features

Beam opening	110°
Nominal flux per mt	1300 lm/m
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	90
Lifespan	35000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	12 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	Yes
Number of cycles	100000
Operating temperature	-25°C / +35°C
Operating position	360°

Photometry

950316 I_{max}=381cd/klm	4000K	H(m)	D1(m)	D2(m)	E _{max} (lx)
	Ra90		102°	111°	
	Fixture Power	12W	1	2.46	2.91 366
	Source Flux	960lm	2	4.92	5.82 91
	Fixture Flux	960lm	3	7.37	8.73 41
	Efficacy	80lm/W	4	9.83	11.64 23
	I _{max}	366cd	5	12.29	14.55 15

EuLumDat file on the site

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Minimum order quantity	1
Minimum packaging	1 / 1