

MULTI-OPTIC RECESSED FIXTURE

Typology
Rectangular recessed fixture for two adjustable GU10 lamps.

Features
Widely used in retail installations, it meets the needs of those who prefer a recessed ceiling luminaire with replaceable lamps.
It offers the advantage of having both multidirectional and adjustable light beams from + 15 ° to -15 ° in the vertical plane.
Houses PAR16 lamps; compatible with all GU10 lamps in the Duralamp catalogue.
Max 30 W.

Installation
Recessed with the special galvanised aluminium springs.
Complete with GU10 lamp holder.

Material
Body in black painted aluminium with silver colour frame.




BASIC | 220-240 Vac | IP20 VI IP23 VO | GU10 | -25°C +45°C

Characteristic data

Input	220-240 Vac	Base	GU10	IP	20	Optical compartment IP	23
Color	Silver gray						

Technisches Datenblattsheet
Fiche technique
Ficha de datos
Technical datasheet
Scheda tecnica

Dimensional characteristics



L	107 mm
L1	202 mm
H	110 mm

Cutting hole	95x190

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Operating temperature	-25°C / +45°C

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	335 gr
Barcode single item	8011905935269
Number of pieces multiple pack	10
Barcode multiple pack	8011905938444
Minimum order quantity	1
Minimum packaging	1 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products