



## OBLÒ RGB 12V AC

### Typology

IP68 LED immersion ceiling light for swimming pools, operating at very low safety voltage.  
Available in cool white or RGB versions.

### Features

Underwater fixture, designed for decorative and functional lighting of swimming pools, installable up to 1 m depth.  
The resistant structure ensures durability and effectively replaces traditional underwater systems consisting of separate lamp, power supply and fixture.  
RGB version: 14 different colours can be selected by pressing the external switch in sequence.

### Material

It is fixed with the supplied screws.  
1.5 m power cable.  
Optional IP68 cable gland, code KTCOON-IP68.

### Power supply

12 V, 50 Hz LED driver not included.

### Notes


Body in ABS and screen in UV-resistant polycarbonate.



### Characteristic data

Power	18 W	Beam	100°	Dimmable	No	Input	12 Vac
Base	Wire	IP	68	Tc	RGB	LED Warranty	G3
IK	IK05	RG	RG1				

### Dimensional characteristics



ø	250 mm
H	41 mm

## Lighting and photometric features

Beam opening	100°
CCT nominal colour temperature	RGB
Colour of the light	RGB
Lifespan	30000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	18 W
Input voltage	12 Vac
Frequency	50/60 Hz
Dimmable	No
Input current	1.5 A
Number of cycles	100000
Operating temperature	-25°C / +35°C

## Other Infotech

Reflector	Yes
-----------	-----

## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-5:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	675 gr
Barcode single item	8011905345358
Number of pieces multiple pack	14
Minimum order quantity	1
Minimum packaging	1 / 14

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products