



RECESSED PROFILES: P023

Features

Reduced width recessed profile with edge protection finishing flaps.
CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:
 12 mm

MAXIMUM POWER:

25W/m

Installation

Recessed.
 Cable outlet aligned with the profile.

Material

Profile in aluminum alloy 6060/6063, anodized 15/20 microns.


Packaging

Aluminum-colored profile kit packaging (code ends with "K"): minimum pack of 5 bars with 5 pairs of end caps and 5 pairs of clips.
 Single profile codes: available as a single bar to be completed with lens and end caps.

Characteristic data

| | | | | | |
|-------|------|--|--|--|--|
| Color | Grey | | | | |
|-------|------|--|--|--|--|

Dimensional characteristics



| | |
|----|---------|
| L | 2000 mm |
| L1 | 17.5 mm |
| L2 | 24.5 mm |
| H | 7.2 mm |

Logistics data

| | |
|--------------------------------|---------------|
| Barcode single item | 8011905344269 |
| Number of pieces multiple pack | 5 |
| Minimum order quantity | 5 |
| Minimum packaging | 5 / 5 |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products