



## SLIMFLUX BL - BASIC

### Typology

Direct lighting LED panel.

### Features

The backlit panel is composed of a metal material back compartment providing a heat sink function.

Do not use with dimmer.

Colour rendering: Ra>80.

### Installation

Installations: recessed, suspended, ceiling/wall.

Surface mounting & adjustable suspension wire kits are available as accessories.

Consider more depth for recessed installations.

### Material

White painted metal body.

Micro-prismatic anti-glare screen.

### Usage information

SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

### Emergency

SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.

### Packaging

6 pieces pack with single items' protection plastic bag.



220-240  
Vac

Ra >80



25000 h  
L70B20

IP20 VI  
IP43 VO

Free Wire

-20°C  
+45°C


Risk  
Group 0



### Characteristic data

Power	40 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Optical compartment IP	43	Flux	4000 lm	PF	>0,9
Tc	4000 K	Ra	>80	LED Warranty	G2	RG	RG0

### Dimensional characteristics



L	595 mm
L1	595 mm
H	34 mm

## Lighting and photometric features

Flux	4000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	>0,9
Operating temperature	-20°C / +45°C

## Other Infotech

Flicker Free	Yes
--------------	-----

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC * Ecodesign 2011/65/EU * RoHS 2012/19/EU * RAEE 2014/30/EU * EMC 2014/35/EU * LVD 2015/863 * Amending RoHS 2017/1369 * Regulation for Energy Labelling 2019/2015 * Regulation for Energy Labelling 2019/2020 * Regulation for Ecodesign 2021/340 * Amending Reg. Energy Labelling 2021/341 * Amending Reg. Ecodesign	CEI EN 55015:2020 (+A11:2020) CEI EN 60598-1:2022 CEI EN 60598-2-1:2022 CEI EN 61000-3-2:2019 (+A1:2021) CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022) CEI EN 61547:2010 CEI EN 62031:2021 (+A11:2022) CEI EN 62471:2010 IEC/TR 62471-2:2009 CEI EN 62493:2015 CEI 34-141:2014
--	--

## Product standards

## Logistics data

Item net weight	1120 gr
Barcode single item	8011905334956
Number of pieces multiple pack	6
Minimum order quantity	6
Minimum packaging	6 / 6

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products