



EXTENDER IP20

Extender IP20

Extender IP20 allows for wireless control with a DALI interface. It generates a local DALI bus with the capacity to drive up to 64 fixtures. It can control groups of fixtures in indoor applications. It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6 A. It prevents any change to the management features provided by the CASAMBI system.

100-240
Vdc

Terminals

Characteristic data

Power	2.7 W	Input	100-240 Vdc	Base	Terminals	PF	0,6
-------	-------	-------	-------------	------	-----------	----	-----

Dimensional characteristics

L	100 mm
H	30 mm

Electrical characteristics

Rated power	2.7 W
Input voltage	100-240 Vdc
Power factor (PF)	0,6

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61347-1:2016 (+A1:2021)
CEI EN 61347-2-11:2002 (+A1:2020)
CEI EN 61547:2010

Logistics data

Item net weight	107 gr
Minimum order quantity	1
Minimum packaging	1 / 1